

ACRYLITE® Gallery acrylic sheet

The Clear Choice for Conservation Glazing



ACRYLITE® Gallery acrylic glazing offers you and your customer numerous advantages over glass which is why it is the clear choice for many museums and galleries. It offers beautiful clarity without heaviness or breakability. And it provides museum-quality protection essential in preserving art and artifacts.

ACRYLITE® Gallery provides what glass can't deliver:

- 10 – 20 times more resistant to impact
- Safer alternative at half the weight
- Easier to handle and install
- More economical to ship
- Exceptional optical clarity

Guaranteed Quality

ACRYLITE® Gallery framing grade (FF3) sheet is the premier acrylic framing grade guaranteed defect free or your money back. It is exceptional general purpose glazing for cherished memorabilia, photographs and prints as well as valued artwork.

Protection from UV Light (OP3 and UV3)

ACRYLITE® Gallery UV filtering provides the highest protection from damaging ultraviolet light, protecting paper-borne artwork, prints and documents from fading, yellowing and brittling. These conservation grades are available in cell cast or extruded sheet and provide exceptional showcasing and enduring protection.

Protection from Glare (P99)

ACRYLITE® Gallery non-glare sheet is designed to minimize glare and reflection and maximize the unhindered viewing of framed artwork and prints. The matte finish shows off the art from almost any angle under typical lighting conditions.

Protection from Abrasion and Chemicals

ACRYLITE® Gallery mar resistant sheet has an abrasion and chemical resistant coating on one or both surfaces. This added protection reduces the risk of scratching or damage when handling. Abrasion resistance and UV filtering properties can be combined for maximum conservation protection. These products can be easily cleaned with common household cleaners such as Windex®.

The Perfect Complement for finishing & maintaining ACRYLITE® Gallery conservation glazing

ACRIFIX® Anti-Static Cleaner

ACRIFIX® AC 1010 antistatic cleaner is the product of choice for maintaining ACRYLITE® Gallery sheet.

It polishes to a streak-free shine while removing grease and dust, and its non-toxic formula is environmentally friendly. ACRIFIX® AC 1010 cleaner is available in 4 ounce, 16 ounce and gallon bottles.

ACRIFIX® Specialty Bonding Agents

ACRIFIX® 2R 0190 Versatile, the quintessential reactive SBA, is viscous, dries clear and bubble-free making it ideal for shadowboxes and vitrines where archival integrity is paramount.

Mix and Match Performance

ACRYLITE® Gallery is versatile and provides a variety of benefits to satisfy your preservation needs. Mix and match the right combination of product attributes for optimum performance.

Performance Benefits of ACRYLITE® Gallery acrylic glazing						
Framing Grades	Defect Free	Conservation UV Filtering	Non-glare Matt Finish	Mar Resistant	Thicknesses	Sheet Sizes*
Extruded						
UV filtering(OP3)	•	•			.098" .118" .177" .236"	48"x96" 51"x100" 60" x 96" 72" x 96" 72" x 120" 48" x 120" 60" x 120" 75" x 126"
UV filtering(UV3)	•	•			.098" .118" .177"	48"x96"
Non-glare (P99)	•		•		.060" .080" .098" .118" .177" .236"	48"x96" 51" x 100" 61" x 97" 61" x 121"
UV filtering with 1-side mar resistant	•	•		•	.098" .118"	48"x96"
UV filtering with non-glare	•	•	•		.098" .118"	48"x96"
Framing grade(FF3)	•				.060" .080" .090" .098" .118" .177" .220"	48"x96" 51" x 100" 60" x 96" 72" x 96" 72" x 120" 48" x 120" 60" x 120" 75" x 126"
Cast						
UV filtering (OP2)	•	•			.118" .177" .236" .354" .472"	48"x96" 72" x 96"
UV filtering mar resistant (OP2 MR1)	•	•		•	.236" .354"	72" x 96"

* Additional sizes available upon request

EVONIK CYRO LLC
1796 Main Street
Sanford, ME 04073 USA
Phone +1 800 631-5384
www.acrylite.net
www.acrylite-shop.com

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Industries is a worldwide manufacturer of PMMA products sold under the ACRYLITE® trademark in the Americas and under the PLEXIGLAS® trademark in the European, Asian, African and Australian continents. Windex® is a registered trademark of the SC Johnson Company.
©2018 Evonik Cyro LLC. All rights reserved. Printed in USA.