

TECHNICAL INFORMATION

ACRYLITE® Soundstop TL-4 System

MASH Compliant Crash Tested System



Example installation of a TL-4 System

Product

The newly designed and crash tested ACRYLITE® Soundstop TL-4 System by Roehm America, LLC offers the impact resistance and safety necessary for elevated roadways, while providing unobstructed views to maintain natural aesthetics and light transmission. Used primarily on highway bridges where safety barriers and the noise barriers attached to them are close to travel lanes and therefore more prone to collisions, the TL-4 system is capable of absorbing an impact without endangering the lives of vehicle occupants or areas under the bridge structure. Performance tested at both the University of Nebraska and Texas A&M Transportation Institute, the TL-4 system prevents vehicle snagging and occupant compartment intrusions; requirements for TL-4 impact standards for attachments to existing roadside safety features. These features, in combination with observed benefits to vehicle stability during test collisions, have resulted in approval by the US Federal Highway Authority (FHWA) of the TL-4 system for use on the National Highway system as an attachment to crash rated concrete barriers.

Features & Benefits

- Offers a safe, yet lightweight system for use on bridges and elevated roadways
- Specifically required where a noise barrier is to be placed in the zone of intrusion (the region above and beyond the face of a traffic barrier where an impacting vehicle may extend during an impact)
- Excellent sound reflecting properties
- Maintains views of surroundings when used with transparent ACRYLITE® Soundstop GS CC panels
- With over 100 Generation I System (NCHRP 350) installations in North America, the history of this system has a proven performance for the safety of the motoring public



MASH Test 4-12 uses a 22,180 lb box truck at 58 mph at a 15° angle which meets the minimum TL-4 criteria of 142 kip-ft.

Specifications

- Patented through US Patent #7,220,007 and Canadian Patent #2,562,204
- Previously crash tested in accordance with NCHRP 350 requirements, Test Level 4 in 2005
- Newly designed and successfully crash tested system in early 2020 now meets updated MASH (Manual for Assessing Safety Hardware) requirements per AASHTO safety guidelines



Still image of the box truck used in the TL-4 MASH Crash Test at Texas A&M Transportation Institute Proving Ground, College Station, TX.



Still image of the heavy duty pick-up truck used in the TL-3 MASH Crash Test at Texas A&M Transportation Institute Proving Ground, College Station, TX.

- Complete turn-key crash tested noise barrier system meets the requirements of AASHTO LRFD Bridge Design Manual
- Approved for use on the National Highway System by the FHWA
- Incorporates ACRYLITE® Soundstop GS CC noise barrier panels with integrated polyamide filaments for fragment retention, meeting international standards, e.g. EN 1794-2
- Lightweight, as little as 100 pounds per linear foot, which reduces the cost of the structure
- Durable, maintenance free panels retain clarity and physical strength despite decades of exposure to sunlight and weather (ASTM D1003 & E1996 test methods)



ACRYLITE® Soundstop GS CC has embedded polyamide filaments to contain broken fragments resulting from collision damage. This complies with EN 1794-2.

Availability

- ACRYLITE Soundstop GS CC sheet is pre-assembled into drop-in style frames
 - Allows for quicker installation times
- Post spacing up to 10 feet wide
 - Fewer anchors and posts also allows for quicker installation times
- Individual frame sizes range from 3 ft – 8 ft
- Multiple frames can be stacked to nearly any height

ACRYLITE® Soundstop GS CC	
Thickness	15, 20, 25 mm
Sheet Size	2m x 3m 2m x 4m 2m x 5m 2.38m x 3.30m
Filament Direction	(-D) black along width (-A) black along length (-J) clear along width (-G) clear along length

ACRYLITE® Soundstop GS CC	
Colors	Color Number
Colorless	0S00
Smoky Brown	8S75
Sky Blue	5S33
Steel Blue	5S31
Midnight Blue	5S34
Spring Green	6S40
Sea Green	6S44
Forest Green	6S41
Danish Green	6S50
Light Grey	7S90
Stone Grey	7S95
Satinice (Frosted)	0S00 SC

“That is the most stable TL-4 crash test I’ve ever seen!”

- Senior FHWA Official in the Office of Safety Design

The following table shows the test conditions for the three MASH tests. All parameters given are actual values, and are within test specifications.

MASH Test Conditions

MASH Test	Vehicle Weight	Impact Speed	Angle of Impact	Impact Severity	Result
4-10 (TL-2)	2,423 lb	63.0 mph	25°	57 kip-ft	Pass
4-11 (TL-3)	5,020 lb	63.2 mph	24.7°	117 kip-ft	Pass
4-12 (TL-4)	22,180 lb	58.5 mph	15°	170 kip-ft	Pass



Time-lapse of MASH 4-10 (TL-2) crash test



Time-lapse of MASH 4-11 (TL-3) crash test



Time-lapse of MASH 4-12 (TL-4) crash test

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether expressed or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technical progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products should be used.

Röhm is a worldwide manufacturer of PMMA products sold under the ACRYLITE® trademark in the Americas and under the PLEXIGLAS® trademark in the European, Asian, African, and Australian continents. ©Roehm America, LLC. All rights reserved.

Printed in the USA.

Roehm America, LLC
 1796 Main Street, Sanford, ME 04037 US
 Phone +1 855 202 7467
 www.acrylite.co