

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

SECTION 1. IDENTIFICATION

Product name : ACRIFIX® 2R 0190

Manufacturer or supplier's details

Company name of supplier : POLYVANTIS GmbH
Address : Riedbahnstraße 70
Weiterstadt HE 64331
Telephone : +49615185012490
Emergency telephone : +1 760 476 3962 (24h) - Account ID: 59904

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Restrictions on use : For professional and industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Hazards for the product as supplied

Flammable liquids : Category 2
Skin irritation : Category 2
Skin sensitization : Category 1
Specific target organ toxicity : Category 3
- single exposure

Other hazards

Vapors may form explosive mixture with air.

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical, ventilating and lighting

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Adhesives
Methacrylic acid ester and additives

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Methyl methacrylate	80-62-6*	>= 60 - <= 80	TSC
Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl)imino]diethanol	-	>= 0.1 - <= 1	TSC
2-(2H-benzotriazol-2-yl)-p-cresol	2440-22-4*	>= 0.1 - <= 1	TSC
Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl)imino]di-2,1-ethanediyl]bis[ω -hydroxy]-	103671-44-9*	>= 0.1 - <= 1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version 1.0 Revision Date: 30.09.2025 SDS Number: 1014-00001 Date of last issue: -
Date of first issue: 09/30/2025

- practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Keep away from direct sunlight.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
Store at room temperature in the original container.
Fill the container by approximately 90 % only as oxygen (air) is required for stabilization. With large storage containers make sure the oxygen (air) supply is sufficient to ensure stability.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures
- Recommended storage temperature : < 86 °F / < 30 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m ³	NIOSH REL
		TWA	100 ppm	OSHA Z-1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

		410 mg/m ³	
--	--	-----------------------	--

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : butyl-rubber
Glove thickness : 0.3 mm
Wearing time : 60 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Appearance	:	liquid
Color	:	violet
Odor	:	ester-like
Odor Threshold	:	0.05 - 0.34 ppm
pH	:	ca. 7 - 8 Concentration: 1 % (as aqueous solution)
Melting point/freezing point	:	-54 °F / -48 °C (1,013 hPa)
Initial boiling point and boiling range	:	ca. 212 °F / 100 °C
Flash point	:	48 °F / 9 °C
Evaporation rate	:	ca. 3
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	ca. 12.5 %(V)
Lower explosion limit / Lower flammability limit	:	ca. 2.1 %(V) (50 °F / 10 °C)
Vapor pressure	:	38.7 hPa (68 °F / 20 °C) (for a component of this mixture)
Relative vapor density	:	> 1
Density	:	ca. 1.02 g/cm ³ (68 °F / 20 °C)
Solubility(ies) Water solubility	:	ca. 16 g/l partly soluble (68 °F / 20 °C)
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	ca. 815 °F / 435 °C
Decomposition temperature	:	The substance or mixture is not classified self-reactive.
Viscosity Viscosity, dynamic	:	1,600 - 2,000 mPa.s (68 °F / 20 °C)
Viscosity, kinematic	:	> 100 mm ² /s (104 °F / 40 °C)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution.

Possibility of hazardous reactions : Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.
Polymerization occurs when exposed to white light, ultraviolet light or heat.
Avoid radical-forming starting agents, peroxides and reactive metals.
Highly flammable liquid and vapor.
Vapors may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Exposure to light.
Heat, flames and sparks.

Incompatible materials : inorganic acid(s)
Free radical initiators
Sulfur compounds
Peroxides
Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents
Oxidizing agents
Amines

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral tox-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

icity

Acute inhalation toxicity : Acute toxicity estimate: 30 - 70 mg/l
Test atmosphere: vapor

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Components:

Methyl methacrylate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Acute oral toxicity : LD50 (Rat, male): 619 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

2-(2H-benzotriazol-2-yl)-p-cresol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Acute oral toxicity : LD50 (Rat, male): 619 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Methyl methacrylate:

Species : Rabbit
Result : Skin irritation

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

2-(2H-benzotriazol-2-yl)-p-cresol:

Species : Rabbit
Result : No skin irritation

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Methyl methacrylate:

Species : Rabbit
Result : No eye irritation
Method : Draize Test

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

2-(2H-benzotriazol-2-yl)-p-cresol:

Species : Rabbit
Result : No eye irritation

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Methyl methacrylate:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	positive
Remarks	:	The test was conducted equivalent or similar to guideline
Assessment	:	Probability or evidence of low to moderate skin sensitization rate in humans

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	positive
Assessment	:	Probability or evidence of skin sensitization in humans

2-(2H-benzotriazol-2-yl)-p-cresol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	positive
Assessment	:	Probability or evidence of low to moderate skin sensitization rate in humans

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	positive
Assessment	:	Probability or evidence of skin sensitization in humans

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

Methyl methacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Inhalation
Result: negative

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 489
Result: negative

2-(2H-benzotriazol-2-yl)-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Hamster
Application Route: Ingestion
Method: OECD Test Guideline 474

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Result: negative

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 489
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Methyl methacrylate:

Species : Mouse
Application Route : Inhalation
Exposure time : 102 weeks
Result : negative

2-(2H-benzotriazol-2-yl)-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Components:

Methyl methacrylate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

2-(2H-benzotriazol-2-yl)-p-cresol:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

May cause respiratory irritation.

Components:

Methyl methacrylate:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

2-(2H-benzotriazol-2-yl)-p-cresol:

Routes of exposure : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Methyl methacrylate:

Species : Rat, male
NOAEL : >= 124.1 mg/kg
Application Route : Ingestion
Exposure time : 104 Weeks

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : Rat, female
NOAEL : 100 mg/kg
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

2-(2H-benzotriazol-2-yl)-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 90 Days

Poly(oxy-1,2-ethanediyl), α,α' -[[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Species : Rat
NOAEL : 100 mg/kg
LOAEL : 400 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Methyl methacrylate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 159.1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 69 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 110 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 110 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : EC10 (Danio rerio (zebra fish)): 16.9 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 37 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50 (activated sludge): 3,162 mg/l
Exposure time: 3 h
Method: ISO 8192

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

2-(2H-benzotriazol-2-yl)-p-cresol:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.17 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

- Toxicity to algae/aquatic plants : EbC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- NOEC (Desmodesmus subspicatus (green algae)): 33 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.013 mg/l
Exposure time: 21 d
- Poly(oxy-1,2-ethanediyl), α,α' -[[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:**
- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Raphidocelis subcapitata (freshwater green alga)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Methyl methacrylate:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 94 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 29 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

2-(2H-benzotriazol-2-yl)-p-cresol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 29 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Methyl methacrylate:

Partition coefficient: n- : log Pow: 1.38
octanol/water

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Partition coefficient: n- : log Pow: 2.17
octanol/water Method: OECD Test Guideline 117

2-(2H-benzotriazol-2-yl)-p-cresol:

Partition coefficient: n- : log Pow: 4.2
octanol/water

Poly(oxy-1,2-ethanediyl), α,α' -[[4-methylphenyl]imino]di-2,1-ethanediyl]bis[ω -hydroxy]-:

Partition coefficient: n- : log Pow: 2.17
octanol/water Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version 1.0 Revision Date: 30.09.2025 SDS Number: 1014-00001 Date of last issue: -
Date of first issue: 09/30/2025

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methyl methacrylate	80-62-6	1000	1464

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Methyl methacrylate 80-62-6 >= 50 - < 70 %
late

US State Regulations

Pennsylvania Right To Know

Methyl methacrylate 80-62-6
2-Propenoic acid, 2-methyl-, methyl ester, polymer with methyl 9011-87-4
2-propenoate

California Prop. 65

WARNING: This product can expose you to chemicals including Methyl acrylate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Methyl methacrylate 80-62-6

California Permissible Exposure Limits for Chemical Contaminants

Methyl methacrylate 80-62-6

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190


Version
1.0

Revision Date:
30.09.2025

SDS Number:
1014-00001

Date of last issue: -
Date of first issue: 09/30/2025

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average

AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® 2R 0190

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2025	1014-00001	Date of first issue: 09/30/2025

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 30.09.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version 1.1 Revision Date: 18.11.2025 SDS Number: 588-00002 Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

SECTION 1. IDENTIFICATION

Product name : ACRIFIX® CA 0020

Manufacturer or supplier's details

Company name of supplier : POLYVANTIS GmbH
Address : Riedbahnstraße 70
Weiterstadt HE 64331
Telephone : +49615185012490
Emergency telephone : +1 760 476 3962 (24h) - Account ID: 59904

Recommended use of the chemical and restrictions on use

Recommended use : Catalyst
Industrial use
Restrictions on use : For professional and industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Hazards for the product as supplied

Skin sensitization : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Disposal:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version 1.1 Revision Date: 18.11.2025 SDS Number: 588-00002 Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Dibenzoyl peroxide	94-36-0*	2.5 - < 10	-

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version 1.1 Revision Date: 18.11.2025 SDS Number: 588-00002 Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Gases

Recommended storage temperature : 50 - 77 °F / 10 - 25 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	ACGIH
		TWA	5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Benzoic acid	65-85-0	TWA (Inhalable fraction and vapor)	0.5 mg/m ³	ACGIH
Benzene	71-43-2	TWA	0.02 ppm	ACGIH
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
		PEL	1 ppm	OSHA CARC
		STEL	5 ppm	OSHA CARC
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm (10 minutes)	OSHA Z-2
Biphenyl	92-52-4	TWA	0.2 ppm	ACGIH
		TWA	0.2 ppm 1 mg/m ³	NIOSH REL
		TWA	0.2 ppm 1 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Minimize workplace exposure concentrations.

Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
- Hand protection
- Material : butyl-rubber
 - Glove thickness : 0.3 mm
 - Wearing time : 480 min
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : yellow
- Odor : characteristic
- Odor Threshold : No data available
- pH : ca. 4 - 5

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version 1.1 Revision Date: 18.11.2025 SDS Number: 588-00002 Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

	Concentration: 1 % (as aqueous solution)
Melting point/freezing point	: < 50 °F / < 10 °C
Initial boiling point and boiling range	: No data available Decomposition
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: 0.0002 hPa (122 °F / 50 °C) (for a component of this mixture)
Relative vapor density	: No data available
Density	: 1.12 g/cm ³ (68 °F / 20 °C)
Solubility(ies) Water solubility	: practically insoluble
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: ca. 752 °F / 400 °C
Decomposition temperature	: > 140 °F / > 60 °C The substance or mixture is not classified self-reactive.
Self-Accelerating decomposition temperature (SADT)	: > 140 °F / > 60 °C
Viscosity Viscosity, dynamic	: 140 mPa.s (68 °F / 20 °C)
Viscosity, kinematic	: > 25 mm ² /s (104 °F / 40 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	: Not applicable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Benzoic acid
Benzene
Phenyl benzoate
Biphenyl

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 3,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 100 mg/l
Test atmosphere: vapor

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Components:

Dibenzoyl peroxide:

Acute oral toxicity : LD50 (Mouse): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC0 (Rat): 24.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Components:

Dibenzoyl peroxide:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Species : Rat
Application Route : Skin contact
Exposure time : 104 weeks
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version 1.1 Revision Date: 18.11.2025 SDS Number: 588-00002 Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

Repeated dose toxicity

Components:

Dibenzoyl peroxide:

Species : Rat
NOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.11 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.0711 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.001 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 35 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Dibenzoyl peroxide:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Biodegradation: 71 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Dibenzoyl peroxide:

Partition coefficient: n-
octanol/water : log Pow: 3.2

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(DIBENZOYL PEROXIDE)
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Dibenzoyl peroxide)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo
aircraft) : 964
Packing instruction (passen-
ger aircraft) : 964
Environmentally hazardous : yes

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

IMDG-Code

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIBENZOYL PEROXIDE)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (Dibenzoyl peroxide)
Class	:	9
Packing group	:	III
Labels	:	CLASS 9
ERG Code	:	171
Marine pollutant	:	yes(Dibenzoyl peroxide)
Remarks	:	Above applies only to containers over 119 gallons (450 liters) in case of liquids, or 882 lbs. (400 kg) in case of solids. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Dibenzoyl peroxide	94-36-0	2.5 - < 10 %
--------------------	---------	--------------

US State Regulations

Pennsylvania Right To Know

Dipropylene Glycol, Dibenzoate	27138-31-4
Ethylene dibenzoate	94-49-5
Dibenzoyl peroxide	94-36-0

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Dibenzoyl peroxide	94-36-0
--------------------	---------

California Permissible Exposure Limits for Chemical Contaminants

Dibenzoyl peroxide	94-36-0
--------------------	---------

California List of Acutely Hazardous Chemicals, Toxics and Reactives

Dibenzoyl peroxide	94-36-0
--------------------	---------

Additional regulatory information

Ethylene dibenzoate	94-49-5
---------------------	---------

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.
See 40 CFR § 721.3025

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020


Version
1.1

Revision Date:
18.11.2025

SDS Number:
588-00002

Date of last issue: 09/09/2025
Date of first issue: 09/09/2025

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

POLYVANTIS

ACRIFIX® CA 0020

Version	Revision Date:	SDS Number:	Date of last issue: 09/09/2025
1.1	18.11.2025	588-00002	Date of first issue: 09/09/2025

Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 18.11.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8